The air purifiers

CleanMaster Pro 22



TEKA Extraction and Waste Disposal Technology Ltd · Millenkamp 9 · 48653 Coesfeld
Tel.: +49 2541 / 84841-0 · Fax: +49 2541 / 84841-72 · Mail: info@teka.eu · Web: www.teka.eu

Product No.: 940170222

Description

CleanMaster Pro 22

The **TEKA CleanMaster Pro 22** is an extraction system for laser fumes and soldering fumes with high air demand. It is used as a mobile or stationary unit, mainly on laser marking systems, at several manual soldering workstations and on soldering systems. The CleanMaster Pro 22 has the same suction power as the Basic 22 plus a bag filter as the first filter stage.

At a glance

- **Four-stage filtration:** bag filter, M5 pre-filter, HEPA H13 main filter, activated carbon
- **Fan:** high negative pressure, even with loaded filters
- **Connection:** spigot for suction hose or pipework
- **Housing:** sheet steel, fully powder-coated

Your benefits

- **For laser fumes and odours:** The activated carbon filter as the final stage absorbs gases and odours produced during laser processing and soldering.
- **Thorough filtration:** A bag filter as the first stage and a large-area pre-filter retain coarser particles before the HEPA H13 filter separates the fine fumes and dust.
- **Consistent performance:** The fan with high negative pressure delivers a high air volume even when the filters are loaded. This allows good filter service life.
- **Tight filter seating:** A built-in filter lifting device ensures that the filters are seated tightly.
- **Safe operation:** The automatic filter monitoring shows when a change is due. A phase sequence indicator in the connection cable warns of incorrect fan rotation.

Applications

Laser marking and laser engraving, several manual soldering workstations, soldering systems with high air demand.

The operating instructions are available in the Downloads tab. Our overview page shows more systems for laser fume extraction.

Properties

Main filter quantity:	1
Prefilter 2:	ISO 16890 ePM10 > 50% (F5)
Volumetric flow (m³/h):	2.000
max. pressure (Pa):	2,800
Engine power (kW):	2.2
Supply voltage (V):	400
Connection frequency (Hz):	50
Current consumption (A):	5
Pre-filter:	G4 bag filter
Vorfilter:	Bag filter ISO 16890 ePM10 coarse > 60% (G4)
main filter:	Filter cartridge
Filter class:	DIN EN 1822 - H13
final filter:	Activated carbon cartridge: 14 kg

TEKA Extraction and Waste Disposal Technology Ltd · Millenkamp 9 · 48653 Coesfeld
Tel.: +49 2541 / 84841-0 · Fax: +49 2541 / 84841-72 · Mail: info@teka.eu · Web: www.teka.eu

Properties

Separation efficiency (%):	> 99.95
Ansaugstutzen (mm):	NW 200
Sound level (dB(A)):	65 – in accordance with DIN EN ISO 3744
Weight (kg):	230
Width (mm):	665
Depth (mm):	1,010
Height (mm):	1,650

TEKA Extraction and Waste Disposal Technology Ltd · Millenkamp 9 · 48653 Coesfeld
Tel.: +49 2541 / 84841-0 · Fax: +49 2541 / 84841-72 · Mail: info@teka.eu · Web: www.teka.eu