

The air purifiers

TEKA

FilterCube 4N, 3.0 kW, 40 m²



(Page: 1 for product 9501440030040100)

Description

Product No.: 9501440030040100

FilterCube 4N, 3.0 kW, 40 m²

The FilterCube 4N stationary filter unit is an IFA-tested filter system that takes up very little space and can be used for an extremely wide range of applications, primarily in the metalworking sector.

Filtration performance of over 99 % ensures that fumes and dusts are reliably separated out. The filter cartridges are cleaned by means of compressed air, meaning that it is not necessary to replace the filters until the through-flow of air is no longer sufficient.

The dust can be removed from the collecting tray very easily. This reduces downtimes to a minimum. The clean air can usually be fed back into the workplace, meaning that during periods in which heating is required, in particular, no new hot air has to be fed into the premises. In this way, the FilterCube helps reduce energy costs.

Standard equipment

- Four standard filter cartridges, with filter surface area depending on air flow rate
- Display-controlled filter cleaning
- Fan control
- Elbow silencer for upward air outlet

Possible options

- Other grades of filter cartridge, with filter surface area depending on air flow rate
- Soundproof housing for fan (reduces the noise level by approx. 6 dB(A))
- Soundproof housing with rear-mounted casing (reduces the noise level by approx. 8 dB(A))
- Hepa filter extension set as final stage (quality H13 with 99.9 % filtration efficiency)
- Activated carbon filter extension set for filtration of gases and odours
- Safety upgrade (particle sensor, compressed air shut-off valve, maintenance door with inspection window for FilterCube 4H/4N with connecting device for CO₂ fire extinguisher)

Possibility of combined use with other TEKA products

- Collecting devices such as suction arms, cranes or suction tables
- Spark separator
- Automatic dosing device for precoating

Properties

Fan design:	auf der Anlage, inkl. Schalldämpfer
Intake manifold (mm):	NW 250 - linke Seite
zu filterndes Medium:	trockener, fettfreier bzw. ölfreier Staub / Rauch
Volumetric flow (m ³ /h):	4.000
max. pressure (Pa):	3.300
Operating point:	3.000 m ³ /h bei 2.600 Pa
Engine power (kW):	3
Supply voltage (V):	400
Connection frequency (Hz):	50
Current consumption (A):	6,6

(Page: 2 for product 9501440030040100)

Properties

Current type:	3Ph+N+PE
Automatic cleaning:	Ja
Filter control:	automatische Filterabreinigung, Siemens S7
Aufbau der Filtersteuerung:	extern mit 5m Kabel
Engine control:	Motorschutzscharter
Aufbau der Motorsteuerung:	integriert in der Filtersteuerung
Vorfilter:	Lochblech als Prallschutz
main filter:	BIA M
Cartridges number:	4 à 10
Hauptfilter Anzahl:	4
Filter surface (m²):	40
Separation efficiency (%):	99
Ausblas:	mittels TEKA-Schalldämpfer, rechte Seite (Ausblas über Gitter 450 x 450 mm*)
Sound level (dB(A)):	78
Width (mm):	800
Depth (mm):	800
Height (mm):	2.320

Replacement parts

Filter cartridge, type standard,
Product No.: 6160600110008




PE-bags (pack of 10) for
Product No.: 10030251

Accessories



Filter cartridge, type easy clean plus
Product No.: 6160600212508



Extension set for FilterCube 4
Product No.: 40009501440



Frequency converter with pressure transmitter for
Product No.: 962002009030



Start-Stop Automatic
Product No.: 150010016



Master-Slave-Control 32A(incl. Transf. for 24V AC)
Product No.: 150010032




Filter cartridge, Type easy clean +
Product No.: 6160600207706



Filter cartridge, Type easy clean nano
Product No.: 6160600307706



Filter cartridge, Type easy clean nano
Product No.: 6160600312606



Extension set H13 filter for FilterCube 4
Product No.: 4000950144002




Mater-Slave-Control 16A (incl. Transf. for 24V AC) Master slave junction box for controlling a motor Option soundproof housing for FilterCube 4

Product No.: 15001001602

Product No.: 15001001604

Product No.: 950144194712



Option soundproof housing for FilterCube 4

Cartridge protection NANNOX P50

Cartridge protection NANNOX P50

Product No.: 950144194718

Product No.: 68130000100

Product No.: 68130000400



Cartridge protection NANNOX P50

Product No.: 68130010000