

The air purifiers



Wet cyclone separator



(Page: 1 for product 20035001577)



Description

Product No.: 20035001577

€16,835.00*

excluding VAT

Wet cyclone separator

The filter unit is appropriate for the filtration of aluminium grinding dust.

As the accumulation of aluminium grinding dust produces a potential risk of explosion, the interior of the WNA-AL protected against sparking due to the explosion-proof engine and the grounded internal parts.

The advantages of the unit are its simple and trouble-free operation. Pumps or jets which could create troubles are not used. The air is cleaned by swirling the dust with water. The particles in the air flow are enclosed by water and bonded.

The extracted dust particles depose in the lower water tank and can be discharged by the ball valve which is installed at the lowest position of the unit and can be extracted through a maintenance flap.

The fan is suitable for continuous operation and is placed onto the unit by standard.

Properties

Fan design:	auf der Anlage
Water consumption (I/h):	4
Water filling quantity during operation (litres):	130
Current type:	3Ph+N+PE
Filter control:	Wasserstandskontrolle, Differenzdruck-Überwachung
Engine control:	motor protection switch
Separation efficiency (%):	> 80
Sound level (dB(A)):	ca. 74
Weight (kg):	ca. 450
Width (mm):	850
Depth (mm):	1.160
Height (mm):	2.660
Colour:	RAL 7016

(Page: 2 for product 20035001577)