The air purifiers

Extraction unit type LFE 101 for laser application



TEKA Absaug- und Entsorgungstechnologie GmbH · Millenkamp 9 · 48653 Coesfeld
Tel.: +49 2541 / 84841-0 · Fax: +49 2541 / 84841-72 · Mail: info@teka.eu · Web: www.teka.eu

Product No.: 9731015

Description

Extraction unit type LFE 101 for laser application

The **TEKA LFE 101** is a mobile cartridge filter unit for laser applications with increased dust generation and is designed for continuous operation. It extracts fumes and fine dust produced during laser engraving, cleaning or cutting. The LFE 101 works with one turbine and has a universal voltage input, so it can be used internationally without an additional transformer.

At a glance

- **Filtration:** baffle plate, three cleanable filter cartridges, activated carbon, HEPA H13 final stage
- **Cleaning:** fully automatic with compressed air, depending on contamination
- **Safety:** particle sensor detects filter breakthroughs and switches off
- **Integration:** Harting interface for control by the laser

Your benefits

- **Stable operation:** While one of the three filter cartridges is being cleaned, the other two continue to extract.
- **Surface filtration:** The easy clean nano cartridges hold the particles on the surface, so they do not penetrate the filter material. No initial precoating is needed.
- **Particles, gases and odours:** After the cartridges, an activated carbon cassette absorbs gases and odours, and the HEPA final stage separates the last fine particles.
- **Easy maintenance:** The cleaned-off particles fall into a dust collection tray that can be removed through a maintenance door. The filter monitoring shows when a change is needed.
- **Operation:** The Siemens S7 control is located in the lid at operating height. The display lets you adjust the suction power continuously.
- **Quiet operation:** The design with separate exhaust air routing reduces the noise level.

Important

A compressed air connection is required for cleaning.

Options

Intake housing in three versions (one of your choice included), spark trap, shut-off valve, exhaust air spigot, automatic dosing unit and, as final stage, an optional ULPA U16 filter.

The operating instructions are available in the Downloads tab. Our overview page shows more systems for laser fume extraction.

Properties

Blower type:	Continuous-flow turbine, single-stage
Control interface:	Harting
Interface description:	Pin 1&2: start-stop, Pin 3: ext. voltage input, Pin 4: ext. fault signal, Pin 5: ext. operation signal, PE=GND
Main filter quantity:	3
Volumetric flow (m³/h):	400
max. pressure (Pa):	7,500
Engine power (kW):	0.6
Supply voltage (V):	115
Connection frequency (Hz):	50/60

TEKA Absaug- und Entsorgungstechnologie GmbH · Millenkamp 9 · 48653 Coesfeld
Tel.: +49 2541 / 84841-0 · Fax: +49 2541 / 84841-72 · Mail: info@teka.eu · Web: www.teka.eu

Properties

Current consumption (A):	6.8
Automatic cleaning:	Yes
Filter control:	Siemens (S7 + LOGO)
Pre-filter:	deflector plate
main filter:	filter cartridge
Filter class:	Dust class M (in accordance with DIN EN 60335-2-69)
Filter surface (m²):	2.7
final filter:	H13 and activated carbon cartridge
Ansaugstutzen (mm):	LFE intake housing
Ausblas:	through the vent openings in the sound-absorbing baffle
Sound level (dB(A)):	68 – in accordance with DIN EN ISO 3744
Weight (kg):	168
Width (mm):	751
Depth (mm):	400
Height (mm):	1,590
Colour:	RAL 9010

Replacement parts



Activated carbon filter 337 x 230 x 212 mm
Product No.: 97059



Hepa filter H13, size 337 x 230 x 100 mm
Product No.: 100350004



Ulpa filter U16, size 337 x 230 x 100 mm
Product No.: 100350005

TEKA Absaug- und Entsorgungstechnologie GmbH · Millenkamp 9 · 48653 Coesfeld
Tel.: +49 2541 / 84841-0 · Fax: +49 2541 / 84841-72 · Mail: info@teka.eu · Web: www.teka.eu



Activated carbon 7,5 kg for LFE unit
Product No.: 100197310



Macrofalt filter G3, 62x62x48mm,
Product No.: 100350008



Filter cartridge, Type easy clean nano
Product No.: 6160600302708



Spare filter mat for Rittal-exhaust fan
Product No.: 5020007079

TEKA Absaug- und Entsorgungstechnologie GmbH · Millenkamp 9 · 48653 Coesfeld
Tel.: +49 2541 / 84841-0 · Fax: +49 2541 / 84841-72 · Mail: info@teka.eu · Web: www.teka.eu