

*The air purifiers*

**TEKA**

# EcoCube basic version 5,5 kW



(Page: 1 for product 20170050)

## Description

# EcoCube basic version 5,5 kW

The EcoCube stationary filter system is an IFA-tested filter system that is very space-saving and can be used for various applications, primarily in metal processing.

Smoke and dust are reliably separated with a filter efficiency of over 99%. The filter cartridges are cleaned with compressed air, so that the filters only need to be replaced when sufficient air flow can no longer be achieved.

The dust can be easily removed from the collection container.

Downtime is therefore kept to a minimum.

The clean air can usually be fed back into the work area, so that no warm air needs to be fed into the hall, especially during the heating season. The

EcoCube thus helps to save energy costs. **Standard**

## equipment

- 4 filter cartridges,  
type easy clean nano, each with a filter area of 25 m<sup>2</sup> - Display-controlled filter  
cleaning - Frequency converter for universal connection 400-480V /  
50/60Hz - Curved silencer for upward air outlet

## Possible options

- Safety upgrade (particle sensor and maintenance door with viewing window and connection device for CO<sub>2</sub> fire extinguisher)

## Possible combination with other TEKA products

- Collection devices such as extraction arms, cranes or extraction tables

## Properties

Fan design:	included in the set, including silencer elbow, right-hand side
medium to be filtered:	dry, grease-free or oil-free dust / smoke
Volumetric flow (m <sup>3</sup> /h):	4,500
Engine power (kW):	5.5
Supply voltage (V):	400 - 480
Connection frequency (Hz):	50/60
Current consumption (A):	11.5
Current type:	3Ph+N+PE
Filter control:	automatic filter cleaning
Engine control:	frequency converter
main filter:	BIA M, Nano model
Cartridges number:	4 to 25

(Page: 2 for product 20170050)

**Properties**

<b>Filter surface (m<sup>2</sup>):</b>	100
<b>Separation efficiency (%):</b>	> 99
<b>Ansaugstutzen (mm):</b>	über Funkenfalle NW 400 mm inkl. Reduzierung auf NW 355 mm, linke Seite
<b>Ausblas:</b>	via silencer elbow
<b>Sound level (dB(A)):</b>	75 + max. 10 during the cleaning pulse
<b>Width (mm):</b>	800
<b>Depth (mm):</b>	800
<b>Colour:</b>	RAL 7016