

The air purifiers



Fan 2000 m³/h



Description

Fan 2000 m³/h

The stable construction qualifies the fan for continuous application. The fan has a high negative pressure of 1500 Pa even at high load. In delivery a snap fastener is included to connect suction arms.

Properties

Volumetric flow (m ³ /h):	2.000
max. pressure (Pa):	1,500
Engine power (kW):	0.75
Supply voltage (V):	230
Connection frequency (Hz):	50
Ansaugstutzen (mm):	NW 150
Ausblas:	NW 150
Sound level (dB(A)):	74 – in accordance with DIN EN ISO 3744
Weight (kg):	27
Width (mm):	449
Depth (mm):	438
Height (mm):	410

Replacement parts



Guard, diam.160mm
Product No.: 41501



Protective motor switch
Product No.: 9620103



Exhaust air hose, diam. 160mm
Product No.: 96303

Accessories



Guard, diam.160mm
Product No.: 41501



Wall bracket for TEKA fan,
Product No.: 96010



Protective motor switch
Product No.: 9620103



Connecting materials diam. 160 mm
Product No.: 96301



Exhaust air hose, diam. 160mm
Product No.: 96303



Sound proofing box
Product No.: 960101



Start Stop Automatic / Incl. magnetic field
sensor
Product No.: 963131220123