

The air purifiers

TEKA

FilterCube 2H, 3.0 kW



(Page: 1 for product 9501421030031300)

Description

Product No.: 9501421030031300

FilterCube 2H, 3.0 kW

The FilterCube 2H stationary filter unit is an IFA-tested filter system that takes up very little space and can be used for an extremely wide range of applications, primarily in the metalworking sector.

Filtration performance of over 99 % ensures that fumes and dusts are reliably separated out. The filter cartridges are cleaned by means of compressed air, meaning that it is not necessary to replace the filters until the through-flow of air is no longer sufficient.

The dust can be removed from the collecting tray very easily. This reduces downtimes to a minimum. The clean air can usually be fed back into the workplace, meaning that during periods in which heating is required, in particular, no new hot air has to be fed into the premises. In this way, the FilterCube helps reduce energy costs.

Standard equipment

- Two standard filter cartridges, with filter surface area depending on air flow rate
- Display-controlled filter cleaning
- Fan control

Possible options

- Other grades of filter cartridge, with filter surface area depending on air flow rate
- Safety upgrade (particle sensor, compressed air shut-off valve, maintenance door with inspection window for FilterCube 2H with connecting device for CO² fire extinguisher)

Possibility of combined use with other TEKA products

- Collecting devices such as suction arms, cranes or suction tables
- Spark separator
- Automatic dosing device for precoating

Properties

Cleaning pressure (bar):	2–4
Compressor capacity (litres per minute):	75
Dust container volume (litres):	50
Fan design:	on the unit in the soundproof enclosure
Filter control structure:	mounted on the housing
fan:	direct drive, low maintenance
medium to be filtered:	dry, grease-free or oil-free dust / smoke
Volumetric flow (m ³ /h):	4.000
max. pressure (Pa):	3,300
Operating point:	3,000 m ³ /h at 2,600 Pa
Engine power (kW):	3
Supply voltage (V):	400

(Page: 2 for product 9501421030031300)

Properties

Connection frequency (Hz):	50
Current consumption (A):	6.6
Current type:	3Ph+N+PE
Automatic cleaning:	Yes
Filter control:	Siemens (S7 + LOGO)
Engine control:	Motor protection switch
Vorfilter:	incl.
main filter:	filter cartridge
Cartridges number:	2 to 15.6
Filter surface (m²):	15.6
Ansaugstutzen (mm):	NW 250 – left or right side
Ausblas:	through the vent openings in the sound-absorbing baffle
Sound level (dB(A)):	76 – in accordance with DIN EN ISO 3744
Width (mm):	665
Depth (mm):	983
Height (mm):	2,670
Colour:	RAL 7016

Replacement parts

Filter cartridge, filter area 15,6m²
Product No.: 6161200115608



PE bags for dust bin, pack of 10
Product No.: 10030250

Accessories



Filter cartridge, filter area 20m²
Product No.: 6161200120008



Filter cartridge, type easy clean plus
Product No.: 6161200225308



Filter cartridge, Typ easy clean plus
Product No.: 6161200215606



Start-Stop Automatic
Product No.: 150010016



Master-Slave-Control 32A (incl. Transf. for
24V AC)
Product No.: 150010032



Filter cartridge, Type easy clean nano
Product No.: 6161200325308



Filter cartridge, Type easy clean nano
Product No.: 6161200315606



Mater-Slave-Control 16A (incl. Transf. for
24V AC)
Product No.: 15001001602



Cartridge protection NANNOX P50
Product No.: 68130000100



Cartridge protection NANNOX P50
Product No.: 68130000400



Cartridge protection NANNOX P50
Product No.: 68130010000