The air purifiers

Wet cyclone separator



TEKA Absaug- und Entsorgungstechnologie GmbH · Millenkamp 9 · 48653 Coesfeld
Tel.: +49 2541 / 84841-0 · Fax: +49 2541 / 84841-72 · Mail: info@teka.eu · Web: www.teka.eu

Product No.: 200350055

Description

Wet cyclone separator

The advantages of the unit are its simple and trouble-free operation. Pumps or jets which could create troubles are not used.
The air is cleaned by swirling the dust with water. The particles in the air flow are enclosed by water and bonded.
The extracted dust particles depose in the lower water tank and can be discharged by the ball valve which is installed at the lowest position of the unit and can be extracted through a maintenance flap.
The fan is suitable for continuous operation and is placed onto the unit by standard.

Properties

Engine control system design:	Sold separately, including cable
Fan design:	on the grounds
Intake opening (mm):	NW 280 – Back
Water consumption (l/h):	approx. 10
Water filling quantity during operation (litres):	approx. 280
Volumetric flow (m³/h):	5.000
max. pressure (Pa):	2,600
Engine power (kW):	5.5
Supply voltage (V):	400
Connection frequency (Hz):	50
Current consumption (A):	11.5
Current type:	3Ph+N+PE
Automatic cleaning:	No
Filter control:	Siemens (S7 + LOGO)
Engine control:	Star-delta connection
Separation efficiency (%):	> 80
Ausblas:	NW 450 – left or right side
Sound level (dB(A)):	74 – in accordance with DIN EN ISO 3744
Weight (kg):	650
Width (mm):	1,250
Depth (mm):	1,560
Height (mm):	3,220
Colour:	RAL 7016

TEKA Absaug- und Entsorgungstechnologie GmbH · Millenkamp 9 · 48653 Coesfeld
Tel.: +49 2541 / 84841-0 · Fax: +49 2541 / 84841-72 · Mail: info@teka.eu · Web: www.teka.eu