

The air purifiers

TEKA

Wet cyclone separator



(Page: 1 for product 200350022)

Description

Wet cyclone separator

The advantages of the unit are its simple and trouble-free operation. Pumps or jets which could create troubles are not used. The air is cleaned by swirling the dust with water. The particles in the air flow are enclosed by water and bonded. The extracted dust particles deposit in the lower water tank and can be discharged by the ball valve which is installed at the lowest position of the unit and can be extracted through a maintenance flap. The fan is suitable for continuous operation and is placed onto the unit by standard.

Properties

Engine control system design:	externally in the control cabinet with a 10 m connection cable
Fan design:	on the grounds
Intake opening (mm):	NW 180 – Back
Water consumption (l/h):	5
Water filling quantity during operation (litres):	180
Volumetric flow (m ³ /h):	2.000
max. pressure (Pa):	2,400
Engine power (kW):	2.2
Supply voltage (V):	400
Connection frequency (Hz):	50
Current consumption (A):	5
Current type:	3Ph+N+PE
Filter control:	Water level monitoring, differential pressure monitoring
Engine control:	Motor protection switch
Separation efficiency (%):	> 80
Ausblas:	About the NW 315 bow silencer – right-hand side
Sound level (dB(A)):	74
Weight (kg):	600
Width (mm):	1,050
Depth (mm):	1,360
Height (mm):	2,575
Colour:	RAL 7016