

The air purifiers

TEKA

filtoo WorkTable



(Page: 1 for product 978300)

filtoo WorkTable

The **TEKA filtoo WorkTable - with work surface attachment and integrated Stavo dust pre-separator** is the ideal solution for a clean and safe working environment. As a mobile **extraction unit**, it reliably captures welding fumes, dust particles, gases and vapors directly at the source and filters the polluted air. The large work surface provides a comfortable capture zone, ensuring that even fine particles from grinding, welding or soldering are safely removed.

The integrated **Stavo dust pre-separator with spark protection and collection tray** ensures particularly efficient pre-separation: a baffle plate directs the airflow towards the tray, where sparks are effectively trapped and coarse dust is separated in advance. This relieves the following four filter stages, extends their service life and reduces operating costs. The collection tray can be emptied easily, making operation especially user-friendly.

With its multi-stage filter system – consisting of coarse filter, pre-filter, main filter and activated carbon filter – the filtoo guarantees highly effective **air purification**. The cleaned air is returned to the working area, eliminating the need for additional exhaust systems. Thanks to its compact design and mobility, the unit can be used flexibly in workshops and production areas.

With over 30 years of experience, TEKA stands for quality “Made in Germany”. The filtoo with work surface attachment convinces with robustness, ease of use and **cost efficiency** – for greater **occupational safety and clean air** in your business

Properties

Load capacity (kg):	30 kg (when stationary)
Main filter quantity:	1
Prefilter 2:	ISO 16890 ePM10 > 50% (F5)
Volumetric flow (m³/h):	1.600
max. pressure (Pa):	1,800
Engine power (kW):	1.1
Supply voltage (V):	230
Connection frequency (Hz):	50

(Page: 2 for product 978300)

Properties

Current consumption (A):	7
Current type:	1PH+N+PE
Pre-filter:	Stavo
Vorfilter:	Coarse filter, ISO 16890 ePM coarse > 45%
main filter:	Main filter (ePM1=80%)
Filter class:	ISO 16890 ePM1 > 80% (F9)
final filter:	activated carbon filter
Weight (kg):	80 (excluding worktop attachment)
Width (mm):	580 (filtoo), 1,150 (worktop attachment)
Depth (mm):	580 (filtoo), 750 (worktop attachment)
Height (mm):	900 (filtoo)
Colour:	RAL 7016

Accessories

Extension set for working surface filtoo
Product No.: 978018

Replacement parts


Gross filter set for filtoo, ViroLine and AirToo
Product No.: 978003




Pre filter for filtoo, ViroLine and AirToo
Product No.: 978004



Main filter for filtoo and AirToo
Product No.: 978005



Activated carbon filter
Product No.: 978006



Retrofit kit STAVO (dust pre-separation)
for
Product No.: 978013